

MFS

Sub-miniature Switches

RoHS Compliant



Common Specifications

Initial contact resistance

Measured at 1.5 mA 200 μ VAC 1kHz

Dielectric strength

Measurement at 500 VAC.


Insulation Resistance

Measured at 500 VDC

Operating temperature range



-10°C ~ +70°C

Part Numbering





MFS101D-6-Z

Non-shorting



PC Hole Layouts

(Top view)



Specifications


Rating	Max.	DC10V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	0.98~2.94N	
Switch timing	Non-shorting	

Switching function (/Viewed from A)	Circuit diagram	No. of terminals
ON	ON	3
2-3	2-1	

Terminal numbers are not shown on the switch.



MFS101D-8-Z

shorting



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC30V 0.3A AC30V 2A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles at DC30V 0.3A 100cycles at AC30V 2A
Operating force		2.45±0.98 N
Switch timing		Shorting

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			3
ON	ON		
2-1	2-3		



MFS101D-9-Z

Non-shorting



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC12V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		0.98±2.94N
Switch timing		Non-shorting

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			3
ON	ON		
2-1	2-3		



☆ **MFS101D-10-Z**

Non-shorting



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		2.94±1.96N
Switch timing		Non-shorting



Switching function (Viewed from A)		Circuit diagram	No. of terminals
			3
ON	ON		
2-3	2-1		

MFS101D-14-Z

Non-shorting

**■ Panel Cut-Out Dimensions**

(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	1.96±0.98N	
Switch timing	Non-shorting	



Switching function (Viewed from A)	Circuit diagram	No. of terminals
		3
ON	ON	
2-1	2-3	

★ **MFS101EA-Z**

[Note] See below.

**■ PC Hole Layouts**

(Top view)



Terminal numbers are not shown on the switch.

■ Specifications


Rating	Max.	DC30V 0.3A AC30V 2A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles at DC30V 0.3A 100cycles at AC30V 2A	
Operating force	2.45±0.98N 1.47±0.98N	
Switch timing	Undefined	

Switching function (Viewed from A)	Circuit diagram	No. of terminals
		4
ON	ON	
3-1	3-2	



: Operating force from the center to the outer side (right or left).
 : Operating force from the outer side (right or left) to the center.

MFS201N-Z

Non-shorting

**■ Panel Cut-Out Dimensions**

(Top view)



Terminal numbers are not shown on the switch.

■ Specifications

Rating	Max.	AC125V 1A • DC30V 1A
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	30mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	300MΩ Min.	
Electrical life	5,000 cycles	
Operating force	0.98~4.9N	
Switch timing	Non-shorting	


Switching function (Viewed from A)	Circuit diagram	No. of terminals
		6
ON	ON	
2-1 5-4	2-3 5-6	

※ : Please note that **MFS101EA-Z** can be either Shorting or Non-shorting.




☆ : Semi-standard products.

MFS201N-4-Z

Non-shorting



PC Hole Layouts
(Top view)



Terminal numbers are not shown on the switch.

Specifications


Rating	Max.	AC125V 1A • DC30V 1A
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	300MΩ Min.	
Electrical life	5,000 cycles	
Operating force	1.47~4.41N	
Switch timing	Non-shorting	

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-1 5-4	2-3 5-6		



☆ : Semi-standard products.

MFS201N-9-Z

Non-shorting



PC Hole Layouts
(Top view)



Terminal numbers are not shown on the switch.


Specifications

Rating	Max.	AC125V 1A • DC30V 1A
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	300MΩ Min.	
Electrical life	5,000 cycles	
Operating force	1.47~4.41N	
Switch timing	Non-shorting	



Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-1 5-4	2-3 5-6		

MFS201N-16-Z

Non-shorting



PC Hole Layouts
(Top view)



Terminal numbers are not shown on the switch.


Specifications

Rating	Max.	AC125V 1A • DC30V 1A
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	2.94±1.47N	
Switch timing	Non-shorting	

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-3 5-6	2-1 5-4		




MFS201N-19-Z

Shorting



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		2.45±0.98N
Switch timing		Shorting

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-1 5-4	2-3 5-6		




★ MFS201N-20-Z

Shorting



■ PC Hole Layouts


(Top view)



Terminal numbers are not shown on the switch.


■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		4.41 ± 1.47N
Switch timing		Shorting

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-1 5-4	2-3 5-6		


MFS201N-21-Z

Non-shorting





■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.




■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		2.45 ± 0.98N
Switch timing		Non-shorting



Switching function (A Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-1 5-4	2-3 5-6		

MFS201N-23-Z

Non-shorting

**PC Hole Layouts**

(Top view)



Terminal numbers are not shown on the switch.


Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	3.92±2.45N	
Switch timing	Non-shorting	



Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-3 5-6	2-1 5-4		

MFS201N-24-Z

Non-shorting

**PC Hole Layouts**

(Top view)



Terminal numbers are not shown on the switch.


Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	1.96±0.98N	
Switch timing	Non-shorting	



Switching function (Viewed from A)		Circuit diagram	No. of terminals
			6
ON	ON		
2-3 5-6	2-1 5-4		

★MFS201PA-4-Z

[Note] See below.

**PC Hole Layouts**

(Top view)



Terminal numbers are not shown on the switch.


Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance	20mΩ Max.	
Dielectric strength	AC500V 1 minute	
Insulation resistance	100MΩ Min.	
Electrical life	5,000 cycles	
Operating force	 2.45±0.98N 1.47±0.98N	
Switch timing	Undefined	

Switching function (Viewed from A)			Circuit diagram	No. of terminals
				8
ON	ON	ON		
3-1 7-5	3-2 7-6	3-4 7-8		




★MFS201PA-5-Z

[Note] See below.



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.

※ : Please note that **MFS201PA-5-Z** can be either Shorting or Non-shorting.


■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		4.41 ^{+1.67} _{-2.16} N
Switch timing		Undefined

Switching function (Viewed from A)			Circuit diagram	No. of terminals
				8
ON 3-1 7-5	ON 3-2 7-6	ON 3-4 7-8		




★MFS401N-2-Z

Shorting



■ PC Hole Layouts

(Top view)



Terminal numbers are not shown on the switch.

■ Specifications

Rating	Max.	DC30V 0.3A (Resistive load)
	Min.	DC5V 10mA (Resistive load)
Initial contact resistance		20mΩ Max.
Dielectric strength		AC500V 1 minute
Insulation resistance		100MΩ Min.
Electrical life		5,000 cycles
Operating force		1.57 N Max. (No detent)
Switch timing		Shorting

Switching function (Viewed from A)		Circuit diagram	No. of terminals
			12
ON	ON		
2-1	2-3		
5-4	5-6		
8-7	8-9		
11-10	11-12		

Soldering

(1)Manual Soldering

Device : Soldering iron
Please refer to “MFS Series Heat-resistant Table” shown below.

(2)Auto Soldering

MFS series are not compatible with auto soldering. Soldering should be done manually.

(3)When soldering two or more terminals to the common land, use solder resist to solder them independently.

MFS series heat-resistant table

Resin board	MFS101D-6-Z	270℃ MAX. 3sec MAX.
	MFS101D-9-Z	
Phenol board	MFS101D-8-Z	360℃ MAX. 3sec MAX.
	MFS201N-19-Z	
	MFS201N-20-Z	
	MFS101D-10-Z	
	MFS101D-14-Z	
	MFS201N-Z	
	MFS201N-4-Z	
	MFS201N-9-Z	
	MFS201N-16-Z	
	MFS201N-21-Z	
	MFS201N-23-Z	
	MFS201N-24-Z	
	MFS201PA-4-Z	
	MFS101EA-Z	
	MFS201PA-5-Z	
	MFS401N-2-Z	


Flux Cleaning

- (1)Solvent : Fluorine or Alcohol type.
- (2)MFS Series are not process sealed. If the PC board is to be cleaned, clean the soldering surface of substrate with a brush so that the switch is not exposed to the cleaning solution.

Frequency of switch use

If the switch is not likely to be operated frequently (e.g. two or three operations a year) in the dry circuit area, a sulfide film is likely to be formed on the contacts, resulting in contact failure. If this is the case, gold-plated products are recommended. Please contact your local Nidec Components sales representative.


Packaging Specifications



■ Shorting (Make-Before-Break) —————

A switch which momentarily connects both circuits when the actuator is moved from Point A to B in the below figure.

All switches which are not marked as “Shorting” are “Non-shorting” (Break-Before-Make).



[Fig.1]
