



SIMATIC S7-1500, digital input module DI 16xNAMUR HF, 16 channels in groups of 8; for 8.2 V NAMUR encoder; sensor supply 8.2 V; input delay; parameterizable 0.05 ... 20 ms; integrated counting function up to 20 kHz pulse stretching; chatter monitoring; signal inversion diagnostics; hardware interrupts; all necessary components for shielding included in the scope of supply; front connector (screw terminals or push-in) to be ordered separately

| General information  |                            |
|--|----------------------------|
| Product type designation   | DI 16xNAMUR HF             |
| HW functional status   | From FS01                  |
| Firmware version   | V1.0.0                     |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>                                     | Yes                        |
| Product function   |                            |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3          |
| <ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>                                       | Yes                        |
| <ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>                                    | Yes                        |
| Engineering with   |                            |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | STEP 7 V17 or higher       |
| <ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>            | V5.5 SP3 / -               |
| <ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>                 | V1.0 / V5.1                |
| <ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>                 | V2.3 / -                   |
| Operating mode   |                            |
| <ul style="list-style-type: none"> <li>DI</li> </ul>   | Yes                        |
| <ul style="list-style-type: none"> <li>Counter</li> </ul>  | Yes                        |
| <ul style="list-style-type: none"> <li>Oversampling</li> </ul>   | No                         |
| <ul style="list-style-type: none"> <li>MSI</li> </ul>  | Yes                        |
| Supply voltage   |                            |
| Rated value (DC)   | 24 V                       |
| permissible range, lower limit (DC)  | 19.2 V                     |
| permissible range, upper limit (DC)  | 28.8 V                     |
| Reverse polarity protection  | Yes                        |
| Input current  |                            |
| Current consumption, max.  | 220 mA                     |
| Encoder supply   |                            |
| Number of outputs  | 16; 2x 8.2 V DC            |
| Short-circuit protection   | Yes                        |
| NAMUR encoder supply   |                            |
| <ul style="list-style-type: none"> <li>8.2 V</li> </ul>  | Yes                        |
| <ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>                               | Yes; Per group, electronic |
| <ul style="list-style-type: none"> <li>Output current, max.</li> </ul>                                   | 100 mA; per group          |
| <ul style="list-style-type: none"> <li>Output current per module, max.</li> </ul>                        | 200 mA                     |
| Power  |                            |
| Power available from the backplane bus   | 0.6 W                      |
| Power loss   |                            |
| Power loss, typ.   | 3.7 W                      |
| Digital inputs   |                            |
| Number of digital inputs   | 16; NAMUR                  |

|   |   |
|---|---|
| Digital inputs, parameterizable   | Yes   |
| Source/sink input   | P-reading   |
| Pulse extension   | Yes; 0.05 s, 0.1 s, 0.2 s, 0.5 s, 1 s, 2 s  |
| Edge evaluation   | Yes; rising edge, falling edge, edge change   |
| Signal change flutter   | Yes; 2 to 32 signal changes   |
| Flutter observation window  | Yes; 0.5 s, 1 s to 100 s in 1-s steps   |
| <b>Digital input functions, parameterizable</b>   |   |
| <ul style="list-style-type: none"> <li>• Gate start/stop</li> <li>• Freely usable digital input</li> <li>• Counter <ul style="list-style-type: none"> <li>— Number, max.</li> <li>— Counting frequency, max.</li> <li>— Counting width</li> <li>— Counting direction up/down</li> </ul> </li> </ul>   | <ul style="list-style-type: none"> <li>Yes; software/hardware gate</li> <li>Yes</li> <li>4; 4 counters max. 10 kHz or 2 counters max. 20 kHz + 2 counters max. 10 kHz; see manual for details</li> <li>20 kHz; See manual for details</li> <li>32 bit</li> <li>Yes; forward / backward</li> </ul> |
| <b>Input voltage</b>  |   |
| <ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>  | 8.2 V   |
| <b>Input current</b>  |   |
| <ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>  | 10 mA   |
| <b>for 10 k switched contact</b>  |   |
| — for signal "0", min.  | 0.35 mA   |
| — for signal "0", max.  | 1.2 mA  |
| — for signal "1", min.  | 2.1 mA  |
| — for signal "1", max.  | 10 mA   |
| <b>for unswitched contact</b>   |   |
| — for signal "0", max. (permissible quiescent current)  | 0.35 to 1.2 mA  |
| — for signal "1", typ.  | 2.1 ... 10 mA   |
| <b>for NAMUR encoders</b>   |   |
| — for signal "0", min.  | 0.35 mA   |
| — for signal "0", max.  | 1.2 mA  |
| — for signal "1", min.  | 2.1 mA  |
| — for signal "1", max.  | 10 mA   |
| <b>Input delay (for rated value of input voltage)</b>   |   |
| <b>for standard inputs</b>  |   |
| — parameterizable   | Yes; 0.05 / 0.1 / 0.4 / 1.6 / 3.2 / 12.8 / 20 ms  |
| — at "0" to "1", min.   | 0.05 ms   |
| — at "0" to "1", max.   | 20 ms   |
| — at "1" to "0", min.   | 0.05 ms   |
| — at "1" to "0", max.   | 20 ms   |
| <b>for interrupt inputs</b>   |   |
| — parameterizable   | Yes   |
| <b>for technological functions</b>  |   |
| — parameterizable   | Yes   |
| <b>for NAMUR inputs</b>   |   |
| — at "0" to "1", max.   | 20 ms   |
| — at "1" to "0", max.   | 20 ms   |
| <b>Cable length</b>   |   |
| <ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>  | 200 m; 200 m for technological functions; depending on input frequency, encoder and cable quality; max. 50 m at 20 kHz  |
| <b>Encoder</b>  |   |
| <b>Connectable encoders</b>   |   |
| <ul style="list-style-type: none"> <li>• NAMUR encoder/changeover contact according to EN 60947</li> <li>• Single contact / changeover contact unconnected</li> <li>• Single contact / changeover contact connected with 10 kΩ</li> <li>• 2-wire sensor <ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>Yes; no CO contact</li> <li>Yes; no CO contact</li> <li>Yes; no CO contact</li> <li>Yes</li> <li>1.2 mA</li> </ul>   |
| <b>Isochronous mode</b>   |   |
| Filtering and processing time (TCI), min.   | 60 μs; At 50 μs filter time   |
| Bus cycle time (TDP), min.  | 250 μs  |
| <b>Interrupts/diagnostics/status information</b>  |   |

|  |  |
|--|--|
| Diagnostics function   | Yes  |
| <b>Alarms</b>  |  |
| • Diagnostic alarm   | Yes  |
| • Hardware interrupt   | Yes  |
| <b>Diagnoses</b>   |  |
| • Monitoring the supply voltage                                | Yes  |
| • Monitoring of encoder power supply                           | Yes; short-circuit   |
| • Wire-break   | Yes; to I < 350 µA   |
| • Short-circuit  | No   |
| <b>Diagnostics indication LED</b>                              |  |
| • RUN LED  | Yes; green LED   |
| • ERROR LED  | Yes; red LED   |
| • Monitoring of the supply voltage (PWR-LED)                   | Yes; green LED   |
| • Channel status display                                       | Yes; green LED   |
| • for channel diagnostics                                      | Yes; red LED   |
| • for module diagnostics                                       | Yes; red LED   |
| <b>Potential separation</b>                                    |  |
| <b>Potential separation channels</b>                           |  |
| • between the channels   | No   |
| • between the channels, in groups of                           | 8  |
| • between the channels and backplane bus                       | Yes  |
| • Between the channels and load voltage L+                     | Yes  |
| • between the channels and the power supply of the electronics | No   |
| <b>Isolation</b>   |  |
| Isolation tested with  | 707 V DC (type test)   |
| <b>Standards, approvals, certificates</b>                      |  |
| Suitable for safety functions                                  | No   |
| <b>product functions / security / header</b>                   |  |
| data integrity   | No   |
| <b>Ambient conditions</b>                                      |  |
| <b>Ambient temperature during operation</b>                    |  |
| • horizontal installation, min.                                | -30 °C   |
| • horizontal installation, max.                                | 60 °C  |
| • vertical installation, min.                                  | -30 °C   |
| • vertical installation, max.                                  | 40 °C  |
| <b>Altitude during operation relating to sea level</b>         |  |
| • Installation altitude above sea level, max.                  | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| <b>Dimensions</b>  |  |
| Width  | 35 mm  |
| Height   | 147 mm   |
| Depth  | 129 mm   |
| <b>Weights</b>   |  |
| Weight, approx.  | 240 g  |

**last modified:** 3/12/2024 